



SECTION 1 - PRODUCT AND COMPANY IDENTIFICATION					
PRODUCT NAME: Test B		PRODUCT NUMBER: 800-6072 (1006150)		DATE: June 11, 2012	
TRADE NAME: Test B – Confirming Test Order					
GENERAL USE: Acid					
CHEMICAL FAMILY: Nitric Acid					
PRODUCT DESCRIPTION: Clear, colorless liquid with acrid odor.					
MANUFACTURER: Safariland LLC		DATE PREPARED: June 11, 2012		SUPERSEDES: April 20, 2012	
ADDRESS (NUMBER, STREET, P.O. BOX): 13386 International Parkway		TELEPHONE NUMBER FOR INFORMATION / Customer Service: 800-347-1200			
(CITY, STATE AND ZIP CODE): Jacksonville, FL. 32218		COUNTRY: USA		CHEMTEL 24-HOUR EMERGENCY TELEPHONE NUMBER  1-800-255-3924 01-813-248-0585 North America Toll Free International	
SECTION 2 - HAZARDS IDENTIFICATION					
EMERGENCY OVERVIEW					
DANGER!!! Product is a poison, strong oxidizer, and a corrosive agent. Causes severe burns to skin, eyes, and respiratory tract. Potentially fatal if swallowed or inhaled. Inhalation may cause lung and tracheal damage. Ingestion may cause tooth, esophageal, and gastric damage. Contact with combustible materials may result in fire. USE CAUTION WITH PRODUCT!!!					
POTENTIAL HEALTH EFFECTS					
INHALATION: Serious irritant to the mucous membranes and respiratory tract, causing potentially severe or fatal burns due to pulmonary edema and/or pneumonia. Symptoms include coughing, choking, burning, sore throat, wheezing, and shortness of breath.					
SKIN: Corrosive substance - may cause severe burns, redness, and pain. Skin may turn yellow and slough off from contact with product. Deep ulcerations that may be slow to heal may develop. Wear personal protective equipment at all times.					
EYES: Both solution and vapors may cause burns, corneal ulcerations or conjunctivitis, leading to permanent eye damage.					
INGESTION: Severe, painful burns of the mouth, throat, esophagus, and stomach will result. Potentially fatal if swallowed. Damage is often irreversible.					
CARCINOGENICITY:					
NTP? NO		IARC MONOGRAPHS? NO		OSHA REGULATED? NO	
CALIFORNIA, Prop.65? NO					
SECTION 3 - HAZARDOUS INGREDIENTS					
Hazardous Components	% (by Weight)	CAS #	EINECS #	Hazard Symbol	RISK PHRASES (Full Text Section 15)
Nitric Acid	NR	7697-37-2	231-714-2	O, C+	R8, R35
Notes:					
SECTION 4 - FIRST AID MEASURES					
Note - prompt, immediate first aid can greatly lessen the damage caused by this product.					
INHALATION: Remove victim to fresh air, providing oxygen or artificial respiration if needed. Seek emergency medical attention promptly.					
EYES: Flush with water for at least 15 minutes. Seek emergency medical help.					
SKIN: Remove contaminated clothing. Rinse with copious amounts of water, using a drench shower if needed. Get medical attention immediately.					
INGESTION: Induce vomiting, if patient is conscious. Give large quantities of water to drink and call a physician immediately.					
SECTION 5 - FIRE FIGHTING MEASURES					
GENERAL HAZARDS: No combustible. Substance is a powerful oxidizer; reactions with combustibles may result in fire. Reacts with metals to generate highly flammable Hydrogen gas.					
EXTINGUISHING MEDIA: Use water spray if needed to cool containers.					
FIRE FIGHTING PROCEDURES: Emergency responders should wear bunker gear and Self-Contained Breathing Apparatus (SCBA). Proper eye and skin protection should also be used. Water spray can be used to cool equipment and reduce vapors.					
UNUSUAL FIRE AND EXPLOSION HAZARDS: May react explosively with combustible organic products. Reacts with metals to generate flammable Hydrogen gas.					
HAZARDOUS COMBUSTION PRODUCTS: Nitrogen Oxides, Carbon Oxides.					

MATERIAL SAFETY DATA SHEET

PRODUCT NAME: Test B
PRODUCT NUMBER: 800-6072 (1006150) **DATE:** June 11, 2012

SECTION 6 - ACCIDENTAL RELEASE MEASURES

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED:

Isolate, then ventilate area. Wear appropriate personal protective equipment, then carefully clean up spill by first containing spill, using dikes if needed. Neutralize with soda ash or lime, then absorb with sand, vermiculite. DO NOT USE SAWDUST TO ABSORB PRODUCT!!! DO NOT RINSE MATERIAL INTO SEWERS OR BODIES OF WATER!

SECTION 7 - HANDLING AND STORAGE

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE:

Store in labeled Acid Cabinet. Keep away from combustibles, metals, direct sunlight, and heat. Do not reuse containers. Always add the acid to water when making solutions; otherwise, uncontrolled boiling and splashing may occur.

SECTION 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

HAZARDOUS COMPONENTS	NIOSH				ACGIH		OSHA	
	TWA ppm	TWA mg/m ³	STEL ppm	STEL mg/m ³	TLV/TWA ppm	TWA mg/m ³	STEL ppm	PEL mg/m ³
Nitric Acid	2	5	4	10	2	5	2	5

PERSONAL PROTECTION

RESPIRATORY PROTECTION:

A NIOSH/OSHA or EU vapor respirator is highly recommended for use with this product. Another option is a fume hood.

PROTECTIVE GLOVES:

Gloves are recommended for use of this product. Consult with glove manufacturer for appropriate glove material.

EYE PROTECTION:

Wear safety goggles as a matter of good laboratory practice while using product. A splash shield should be used while pouring.

OTHER PROTECTIVE CLOTHING OR EQUIPMENT:

An acid-resistant apron or hazard suit is essential for safe handling of Nitric Acid.

WORK / HYGIENIC PRACTICES:

Do not smoke, eat, or drink while using this product. Immediately wash hands after use. Always wear the proper personal protective equipment and observe good laboratory practices.

SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE AND ODOR Clear, colorless liquid with acrid odor.	VAPOR PRESSURE <3.0 mm Hg at 20°C (68°F)
pH <1.0 (HIGHLY ACIDIC AND CORROSIVE)	SPECIFIC GRAVITY (WATER = 1) 1.5
BOILING POINT / BOILING RANGE <122°C (252°F)	SOLUBILITY IN WATER Soluble
MELTING POINT -42°C (-44°F)	VISCOSITY NA
FLAMMABLE LIMITS LEL: NE UEL: NE	VAPOR DENSITY (AIR = 1) 2-3
PERCENT VOLATILE 100%	EVAPORATION RATE (WATER = 1) NE

SECTION 10 - STABILITY AND REACTIVITY

STABILITY STABLE X	CONDITIONS TO AVOID: Excessive heat, light.
---------------------------	---

INCOMPATIBILITY (MATERIALS TO AVOID):

Combustible Organics, Metals, Strong Bases, Carbides.

HAZARDOUS DECOMPOSITION OR BYPRODUCTS:

Nitrogen Oxides.

HAZARDOUS POLYMERIZATION:

Will not occur.

CONDITIONS TO AVOID:

None related to polymerization.

SECTION 11 - TOXICOLOGICAL INFORMATION

Hazardous Components	CAS # EINECS #	LD50 of Ingredient (Specify Species and Route)	LC50 of Ingredient (Specify Species)
Nitric Acid	7697-37-2 231-714-2	Lowest published lethal dose: 430 mg/kg (human)	Inhalation rat LC50: 244 ppm (NO2)/ 30 Minutes

SECTION 12 - ECOLOGICAL INFORMATION

Concentrated product will corrode sewer systems. Large quantities will cause harm to aquatic life. Do not release product into sewer systems or bodies of water.

SECTION 13 - DISPOSAL CONSIDERATIONS

WASTE DISPOSAL METHOD:

Dispose of product waste as well as containers in accordance with all local, state and federal regulations.

MATERIAL SAFETY DATA SHEET

PRODUCT NAME:	Test B	DATE:	June 11, 2012
PRODUCT NUMBER:	800-6072 (1006150)		

SECTION 14 - TRANSPORT INFORMATION

GROUND SHIPMENT WITHIN USA (DOT):

PROPER SHIPPING NAME: Nitric Acid, UN2031. None when shipped under 49CFR173.4b (GROUND ONLY)
 CLASS/ PACK GROUP/ LABELING: Class 8 (5.1).Pack Group II.

NOTES: When shipped under 49CFR173.4b, This product is exempt from other labeling and waybill requirements.
 Total package volume must not exceed 100 mL / package weight ≤ 64 lbs / 29 kg.

GROUND SHIPMENTS TO AND WITHIN CANADA (TDG):

PROPER SHIPPING NAME: Nitric Acid, UN 2031 (GROUND ONLY / CARGO ONLY)
 CLASS/ PACK GROUP/ LABELING: Class 8 (5.1) Pack group II. Excepted & Limited Quantities forbidden.

NOTES: **MUST USE TDG REQUIRED LABELING FOR SHIPMENT INTO CANADA**

AIR SHIPMENTS (ICAO/IATA):

PROPER SHIPPING NAME: Nitric Acid (65-70%), UN 2031
 CLASS/ PACK GROUP/ LABELING: Class 8 (5.1) Pack group II. Excepted & Limited Quantities forbidden.

NOTES: Full documentation required.

OCEAN SHIPMENTS (IMDG):

PROPER SHIPPING NAME: Nitric Acid (65-70%), UN 2031
 CLASS/ PACK GROUP/ LABELING: Class 8 with Excepted Qty. marking on package. No class 8 or 5.1 label required.

NOTES: Shipping Paper required with statement "Dangerous Goods in Excepted Quantities" and number of packages.

ALL SHIPMENTS EXCEEDING EXCEPTED QUANTITY / ALTERNATIVE SHIPPING INFORMATION:

PROPER SHIPPING NAME: See IATA requirements
 CLASS/ PACK GROUP/ LABELING: Class 8 , 5.1, Pack group II, Oxidizer and Corrosive labels.

NOTES: Full documentation required.

Note: Transportation information provided is for reference only. Client is urged to consult CFR 49 parts 100 - 177, IMDG, IATA, TDG & UN information manuals for detailed regulations and exceptions covering specific container sizes, packaging materials and methods of shipping.
Information above does not account for overpacks or outer packings with multiple hazardous materials; consult shipper when multiple materials are shipped. Consult regulations for maximum outer packaging and overpack requirements



SECTION 15 - REGULATORY INFORMATION

TSCA (USA - Toxic Substance Control Act):	Components Listed.
SARA TITLE III (USA - Superfund Amendments and Reauthorization Act):	NO
Acute Health: YES	Chronic Health: YES
Fire: NO	Sudden Release of Pressure: NO
Reactive: YES	


313 REPORTABLE INGREDIENTS: Yes - Nitric Acid
 CERCLA (USA - Comprehensive Response Compensation and Liability Act): **1000 pd RQ (454kg) for Nitric Acid**
 California Prop 65, Safe Drinking Water and Toxic Enforcement Act of 1986: **Not listed.**

State Right to Know: **Nitric Acid, ILL, MA, NJ, PA, RI.**
 CPR (Canadian Controlled Products Regulations): **Not listed.**
 IDL (Canadian Ingredient Disclosure List): **Listed.**
 DSL / NDSL (Canadian Domestic Substances List / Non-Domestic Substances List): **Components listed on DSL.**
 EINECS (European Inventory of Existing Commercial Chemical Substances): **Referenced.**

WGK Water Quality Index: **2**

RISK PHRASES:	SYMBOL(S) REQUIRED FOR EU LABEL	SAFETY PHRASES:
<p>R8 : Contact with combustible material may cause fire. R35 : Causes severe burns.</p>	 C+- Highly Corrosive  O - Oxidizer	<p>S1/2 : Keep locked up and out of the reach of children. S23 : Do not breathe gas/fumes/vapor/spray (appropriate wording to be specified by the manufacturer). S26 : In case of contact with eyes, rinse immediately with plenty of water and seek medical advice. S36 : Wear suitable protective clothing. S45 : In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible).</p>

MATERIAL SAFETY DATA SHEET

PRODUCT NAME: Test B		DATE: June 11, 2012	
PRODUCT NUMBER: 800-6072 (1006150)			
SECTION 16 - OTHER INFORMATION			
Legend: NA = Not Applicable, NE = Not Established, ND = Not Determined, NR = Not Reported			
HMIS HAZARD RATINGS	HEALTH: FLAMMABILITY: PHYSICAL HAZARD: PERSONAL PROTECTIVE EQUIPMENT:	4 0 3 B	0 = INSIGNIFICANT 1 = SLIGHT 2 = MODERATE 3 = HIGH 4 = EXTREME
REVISION SUMMARY: Revised 6/11/2012			
MSDS Prepared by: ChemTel Inc. 1305 North Florida Avenue Tampa, Florida USA 33602-2902 Toll Free North America 1-888-255-3924 Intl. +01 813-248-0573 Website: www.chemtelinc.com			
The information contained herein is believed to be accurate but is not warranted to be so. Data and calculations are based on information furnished by the manufacturer of the product and manufacturers of the components of the product. Users are advised to confirm in advance of need that information is current, applicable and suited to the circumstances of use. Vendor assumes no responsibility for injury to vendee or third persons proximately caused by the material if reasonable safety procedures are not adhered to as stipulated in the data sheet. Furthermore, vendor assumes no responsibility for injury caused by abnormal use of this material even if reasonable safety procedures are followed. Any questions regarding this product should be directed to the manufacturer of the product as described in Section 1.			