Material Safety Data Sheet

SUDAN BLACK (Premix)

SECTION 1- IDENTITY					
NAME ADDRESS ADDRESS					
Evident Crime Scene Products TELEPHONE			oad, Union Hall, VA 241		DDATED:
800-576-7606	FOR ADDITIONAL INFORMATION CONTACT: Technical Support			DATE PREPARED/UPDATED: January 1, 2010	
COMMON NAME (USED ON LABEL)			CHEMICAL FAMILY:		
Sudan Black Premix				N/A (Chemical mixture)	
CHEMICAL NAME: Does Not Apply	FORMULA: TRADE NAME & SYNONYMS: Does not apply Naphthol Blue-Black B				
SECTION 2- HAZARDOUS INGREDIENTS					
HAZARDOUS COMPONENT			CAS#	PEL	TLV
ETHYLENE GLYCOL			107-21-1	50 ppm	50 ppm
ACETIC ACID			64-19-7	25mg/M3	25mg/M3
METHANOL			67-56-1	200 ppm	200 ppm
PEL: Permissible Exposure Limit established by Occupational Safety and Health Administration					
TLV: Threshold Limit Value established by the American Conference of Governmental Industrial Hygienists					
PHYSICAL DATA					
BOILING POINT: 64.7C (Methanol)	SPECIFIC GRAVITY: 0.791 MeOH	VAPOR PRESSURE: 410mm @ 50C		VAPOR DENSITY: 1 (Methanol)	
196C (Ethylene Glycol)	1.113 Ethylene Glycol	0.08		2.1 (Ethylene Glycol)	
PERCENT VOLATILE (VOL)	SOLUBILITY (WATER)	REACTIVITY IN WATER:		EVAPORATION RATE:	
95%+	90%+ None			High (MeOH)	
APPEARANCE AND ODOR: Brown to black-colored liquid, Alcohol Odor					
SECTION 4- FIRE AND EXPLOSION DATA					
FLASH POINT:	AUTO IGNITION TEMPER	ATURE		IN AIR (% by VOLUME)	
52C (Methanol)	725C (Methanol)		LOWER: 6% (Meti	hanol) l	JPPER: 36%
109C (Ethylene Glycol)	399C (Ethylene Glycol)		(Methanol)	hylene Glycol)	15.3%
			(EthyGly)	riylerie Giycor)	13.3 /0
EXTINGUISHING MEDIA:					
Carbon Dioxide, Dry Chemical, water mist, UNUSUAL FIRE AND EXPLOSION HAZARDS:					
Emits toxic fumes under fire conditions					
SPECIAL FIRE FIGHTING PROCEDURES:					
Wear self-contained breathing apparatus and protective clothing					
The above information is believed to			REVERSE SIDE	y used only as a guida. To	vident Crime Seens
The above information is believed to be correct, but does not purport to be all inclusive and shall be used only as a guide. Evident Crime Scene Products & Crime Scene Supply, Incorporated shall not be held liable for any damage or injury to any party, or second party, or bystander resulting					
from the use, handling, or from contact with the above product.					

MSDS PAGE 2 SUDAN BLACK PREMIX MSDS PAGE 2

SECTION 5- HEALTH INFORMATION

PRIMARY ROUTES OF EXPOSURE

Inhalation, ingestion, or absorption through skin

SIGNS & SYMPTOMS OF EXPOSURE

1: ACUTE OVEREXPOSURE:

May cause eye, skin, or respiratory irritation, light headedness Ethylene Glycol is highly toxic- Ingestion can cause death

2: CHRONIC OVEREXPOSURE:

Ethylene Glycol is highly toxic- Ingestion can cause death

MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE:

May cause eye, skin, or respiratory irritation

CHEMICAL /COMPONENT LISTED AS CARCINOGEN OR POTENTIAL CARCINOGEN:

None

OTHER EXPOSURE LIMITS:

Not established

EMERGENCY & FIRST AID PROCEDURES:

EYES: Flush with cool tap water for at least 15 minutes

SKIN: Wash thoroughly with warm water

RESPIRATORY: Remove to fresh air, if distress continues, administer oxygen and contact physician`

INGESTION: Drink large amounts of water, do not induce vomiting

IN ALL CASES IF IRRITATION OR DISTRESS PERSISTS. CONTACT PHYSICIAN OR NEAREST POISON CONTROL CENTER

SECTION 6- REACTIVITY DATA

STABILITY: CONDITIONS TO AVOID:

Stable High Temperatures, Sources of ignition, Open flame

INCOMPATIBILITY (MATERIALS TO AVOID):

Strong Oxidizing agents

HAZARDOUS DECOMPOSITION PRODUCTS:

Carbon Monoxide and Carbon Dioxide on combustion

HAZARDOUS POLYMERIZATION:

Will not occur

Not applicable for polymerization

SECTION 7- SPILL OR LEAK PROCEDURES

STEPS TO BE TAKEN IN CASE MATERIAL IS LEAKED OR SPILLED:

Eliminate all sources of ignition. Wear protective equipment. For small spills, absorb on sand, vermiculite, or other approved absorbent and containerize for toxic disposal If dry- clean up spill in a manner which minimizes dust spread.

CONDITIONS TO AVOID (POLYMERIZATION)

WASTE DISPOSAL METHOD:

Dispose of wastes in accordance with current Federal, State, and Local codes and guidelines.

SECTION 8- PERSONAL PROTECTION INFORMATION

RESPIRATORY PROTECTION:

NIOSH/MSHA Approved Organic Vapor Respirator

VENTILATION:

Room ventilation is expected to be adequate except during spills or fires.

PROTECTIVE GLOVES:

Chemical resistant gloves

EYE PROTECTION:

Suggested when the potential of splashes or contact with the eyes or face is possible

OTHER PROTECTIVE CLOTHING OR EQUIPMENT:

An eye wash fountain and safety shower should be readily available where the potential for splashes or eye contact with the reagent exists

SECTION 9- SPECIAL PRECAUTIONS

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING:

Store and handle according to package and MSDS directions. Store in cool, well-ventilated area. Keep away from reactive materials and away from fire hazard or source of ignition.

OTHER PRECAUTIONS:

Do not ingest, get in eyes, on skin, or on clothing. Avoid breathing dust or vapor. Wash thoroughly after handling. Ethylene Glycol is highly toxic- Ingestion can cause death

TRANSPORTATION

Shipping Name: Methanol Solution Hazard Class: 3 UN# 1230 Packing Group: II Flammable Liquid

The above information is believed to be correct, but does not purport to be all inclusive and shall be used only as a guide. Evident Crime Scene Products & Crime Scene Supply, Incorporated shall not be held liable for any damage or injury to any party, or second party, or bystander resulting from the use, handling, or from contact with the above product.