## SECTION 1 - PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME: Test C

PRODUCT NUMBER(S): 800-6073 (1006151) DATE: April 20, 2012

TRADE NAME: Test C – Barbiturates

GENERAL USE: Presumptive Test Kit for Barbiturates

CHEMICAL FAMILY: NA
PRODUCT DESCRIPTION:

1st Ampoule - Pink color with odor of alcohol.

2nd Ampoule - Clear liquid with odor of Isopropylamine

(ammonical odor).

MANUFACTURED FOR:

DATE PREPARED:

April 20, 2012

Safariland LLC

SUPERSEDES:

July 15, 2011

ADDRESS (NUMBER, STREET, P.O. BOX)

TELEPHONE NUMBER FOR INFORMATION / Customer Service

13386 International Parkway 800-347-1200

(CITY, STATE AND ZIP CODE) COUNTRY CHEMTEL 24-HOUR

Jacksonville, FL 32218 USA



PUBLIC SAFET

**1-800-255-3924 01-813-248-0585**North America Toll Free International

## SECTION 2 - HAZARDS IDENTIFICATION

ChemTel

#### EMERGENCY OVERVIEW

Flammable liquid and vapors. Toxic if swallowed; may cause blindness. Cannot be made non-poisonous. Vapors may cause irritation and drowsiness or dizziness.

#### POTENTIAL HEALTH EFFECTS

#### INHALATION:

Irritation of throat. Inhalation of vapors and or Isopropylamine may be injurious to the lungs and with repeated inhalation chronic irritation/inflammation of nose, throat, and bronchial tubes. Isopropylamine irritates mucous membranes and respiratory tract, and causes severe irritation, blisters, and burns on prolonged contact. Methanol causes Cough. Dizziness. Headache. Nausea. Weakness. Visual disturbance. May be harmful if inhaled.

#### SKIN:

Irritation and or burns by direct contact. Delayed onset contact dermatitis is also possible with chronic repeated exposure to both ampoule 1 and ampoule 2 chemicals.

## EYES:

Chronic irritation of eyes, corneal burns are possible with exposure to Isopropylamine. (Ampoule 2). Methanol is toxic to eyes.

## INGESTION:

Severe irritation and ulceration of the gastrointestinal tract. Vomiting and diarrhea are also symptoms. Will cause CNS depression, kidney liver and eye damage if ingested. Very toxic by ingestion! Shortness of breath. Vomiting. Convulsions. Unconsciousness. (Further see Inhalation).

CARCINOGENICITY:

NTP? No IARC MONOGRAPHS? No OSHA REGULATED? No

CALIFORNIA, Prop.65? NO ESIS? NO

CECTION O MAZARROUG MORERIENTO						
SECTION 3 - HAZARDOUS INGREDIENTS						
Hazardous Components	% (by Weight)	CAS#	EINECS#	Hazard Symbol	RISK PHRASES (Full Text Section 15)	
Methanol 1st ampoule	>90	67-56-1	200-659-6	F, T	R11, R23/24/25, R39/23/24/25.	
Methanol, 2nd Ampoule	>90	67-56-1	200-659-6	F, T	R11, R23/24/25, R39/23/24/25.	
Isopropylamine: 2nd Ampoule	<10	75-31-0	200-860-9	F+, Xi	R12, R36/37/38	
Notes: Hazard symbols and risk	phrases base	ed on maximum listed conc	entration of each hazardous in	ngredient.	•	

PRODUCT NAME: Test C

PRODUCT NUMBER(S): 800-6073 (1006151) DATE: April 20, 2012

## SECTION 4 - FIRST AID MEASURES

INHALATION:

Remove to fresh air, apply CPR if victim is unconscious, administer oxygen, seek immediate medical attention.

FYFS:

In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. Seek immediate medical attention.

SKIN:

In case of contact, immediately flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes. Seek medical attention.

#### INGESTION:

If swallowed, give plenty of water to dilute substances, do not induce vomiting; if conscious, give large quantities of water immediately to dilute the Isopropylamine. If vomiting occurs spontaneously, keep the head below the waist to avoid aspiration. Call a physician immediately.

## SECTION 5 - FIRE FIGHTING MEASURES

#### GENERAL HAZARDS:

Isopropylamine emits toxic and irritating gases when involved in a fire. Vapors may travel considerable distance to source of ignition and flash back. Water spray may be ineffective as extinguishing agent.

#### EXTINGUISHING MEDIA:

Use extinguishing media such as foam, CO2 or dry chemical for Methanol and Isopropylamine. Water may be ineffective.

#### FIRE FIGHTING PROCEDURES:

Use NIOSH/MSA or European EN-149 approved respirators rated for strong bases such as ammonia for Ampoule 2 fires, or SCBA equipment.

#### UNUSUAL FIRE AND EXPLOSION HAZARDS:

Under fire conditions wearing NIOSH/MSA or European EN-149 approved respirators or SCBA's is required. Vapors may travel considerable distance to source of ignition and flash back. Water spray may be ineffective as extinguishing agent.

#### HAZARDOUS COMBUSTION PRODUCTS:

Hazardous vapors may form from heated material.

## SECTION 6 - ACCIDENTAL RELEASE MEASURES

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED:

Wear protective equipment; ventilate area; absorb on paper towels or vermiculite and dispose as hazardous waste.

## SECTION 7 - HANDLING AND STORAGE

## PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE:

Store and handle according to packaged instructions. Store in cool, well ventilated area. Keep away from reactive materials and sources of ignition. Avoid breathing Isopropylamine / Methanol vapor and prevent vapor accumulation in enclosed areas.

#### SECTION 8 - EXPOSURE CONTROLS / PERSONAL **PROTECTION** NIOSH **ACGIH OSHA** TLV/TWA ppm TWA ppm STEL ppm STEL mg/m3 STEL mg/m3 TWA mg/m3 TWA mg/m3 STEL ppm HAZARDOUS COMPONENTS Methanol 1st&2nd ampoules 200 6000 IDLH 200 200 5 5 Isopropylamine: 2nd Ampoule 5 **750 IDLH** 12

#### PERSONAL PROTECTION

RESPIRATORY PROTECTION:

NIOSH/MSA or European EN-149 approved ammonia vapor respirator for minor Isopropylamine spills.

# PROTECTIVE GLOVES:

Impervious gloves (neoprene, nitrile) required when any contact potential with contents exists.

### EYE PROTECTION:

Do not get in eyes, wear safety glasses with side shield splash protection or chemical goggles.

### OTHER PROTECTIVE CLOTHING OR EQUIPMENT:

An eye wash fountain and safety shower should be readily available where the potential for contact exists.

### WORK / HYGIENIC PRACTICES:

Wash thoroughly after handling. Be prepared to clean up toxic Isopropylamine.

PRODUCT NAME: Test C PRODUCT NUMBER(S): 800-6073 (1006151) April 20, 2012 DATE: SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES APPEARANCE AND ODOR VAPOR PRESSURE 1st Ampoule - Pink color with odor of alcohol. 97 mm Hg - Ampoule 1 2nd Ampoule – Clear liquid with odor of Isopropylamine 331 mm Hg- Ampoule 2 (ammonical odor). NE SPECIFIC GRAVITY (WATER = 1) VOC Volatility NE 0.8 (Ampoule 1), 0.79 (Ampoule 2) BOILING POINT / BOILING RANGE SOLUBILITY IN WATER Soluble 33-34°C(91-94°F) Isopropylamine, 65°C(149°F) Methanol FLASH POINT VISCOSITY 54°F (12°C) Ampoule 1, 63°F (79°C) Ampoule 2 NA FLAMMABLE LIMITS VAPOR DENSITY (AIR = 1) LEL: 6% 1.1 (Ampoule 1), 1.15 (Ampoule 2) UEL: 36% EVAPORATION RATE (WATER = 1) **AUTO-IGNITION TEMPERATURE** 867°F (464°C) Ampoule 1, 756°F (402°C) Ampoule 2 5.9 (Ampoule 1), 23.9 (Ampoule 2) SECTION 10 - STABILITY AND REACTIVITY STABILITY **STABLE** CONDITIONS TO AVOID: X Excessive heat, contact with incompatible materials. INCOMPATIBILITY (MATERIALS TO AVOID): Oxidizers such as permanganates, chromium trioxide, perchlorates, periodates. HAZARDOUS DECOMPOSITION OR BYPRODUCTS: Toxic gases and vapors (such as oxides of nitrogen and carbon monoxide) may be released in a fire involving Isopropylamine. HAZARDOUS POLYMERIZATION: CONDITIONS TO AVOID: Will not occur. None related to polymerization. **SECTION 11 - TOXICOLOGICAL INFORMATION** CAS# LD50 of Ingredient LC50 of Ingredient **Hazardous Components EINECS#** (Specify Species and Route) (Specify Species) Oral LD50 Rat=5,600mg/Kg. Inhalation LD-Lo 67-56-1 Oral LDLo Human=143mg/kg Human=300ppm. Methanol 1st&2nd ampoules 200-659-6 Oral, rat LD50=111mg/kg Inhalation rat 75-31-0 LC50=4000ppm/4hour. Isopropylamine, 2nd Ampoule 200-860-9 **SECTION 12 - ECOLOGICAL INFORMATION** Hamrful to environment when released in large quantities. Product is readily biodegradable. **SECTION 13 - DISPOSAL CONSIDERATIONS** 

# WASTE DISPOSAL METHOD:

Chemical waste generators must determine whether a discarded chemical is classified as a hazardous waste. US EPA guidelines for the classification determination are listed in 40 CFR Parts 261.3. Additionally, waste generators must consult state and local hazardous waste regulations to ensure complete and accurate classification. Do not allow isopropylamine or isopropanol to enter a sewer because of the possibility of an explosion.

PRODUCT NAME: Test C

PRODUCT NUMBER(S): 800-6073 (1006151) DATE: April 20, 2012

**SECTION 14 - TRANSPORT INFORMATION** 

GROUND SHIPMENT WITHIN USA (DOT):

PROPER SHIPPING NAME: None - Exempted Qty.

CLASS/ PACK GROUP/ LABELING: Class 3 (6.1) with Excepted Qty. marking on package. No class 3 or 6.1 label

required.

NOTES: When shipped under 49CFR173.4a, This product is exempt from other labeling and waybill requirements.

GROUND SHIPMENTS TO AND WITHIN CANADA (TDG):

PROPER SHIPPING NAME: None - Limited Quantity (within Canada), See above for US to Canada

CLASS/ PACK GROUP/ LABELING: Phrase "Ltd. Qty." on package. No additional requirements.

NOTES: TDG only used for shipment within Canada, shipments from the US can follow DOT regulations. See TDG

Sections 1.17 and 9.

AIR SHIPMENTS (ICAO/IATA):

PROPER SHIPPING NAME: None - (Classified under UN1230 Methanol Solution - Excepted Qty. E2)

CLASS/ PACK GROUP/ LABELING: Class 3 (6.1) with Excepted Qty. marking on package. No class 3 or 6.1 label

required.

NOTES: This product is exempt from other labeling and waybill requirements.

OCEAN SHIPMENTS (IMDG):

PROPER SHIPPING NAME: None

CLASS/ PACK GROUP/ LABELING: Class 3 (6.1) with Excepted Qty. marking on package. No class 3 or 6.1 label

required.

NOTES: Shipping Paper required with statement "Dangerous Goods in Excepted Quantities" and number of packages.

ALL SHIPMENTS EXCEEDING EXCEPTED QUANTITY / ALTERNATIVE SHIPPING INFORMATION:

PROPER SHIPPING NAME: UN 3316, Chemical Kit

CLASS/ PACK GROUP/ LABELING: Class 9, Pack Group III. Miscellaneous Label

NOTES: Full documentation required.

Note: Transportation information provided is for reference only. Client is urged to consult CFR 49 parts 100 - 177, IMDG, IATA, TDG & UN information manuals for detailed regulations and exceptions covering specific container sizes, packaging materials and methods of shipping. Information above does not account for overpacks or outer packings with multiple hazardous materials; consult shipper when multiple materials are shipped. Consult regulations for maximum outer packaging and overpack requirements

SECTION 15 - REGULATORY INFORMATION

TSCA (USA - Toxic Substance Control Act): Ingredients are listed.

SARA TITLE III (USA - Superfund Amendments and Reauthorization Act):

Acute Health: Yes Chronic Health: Yes Reactive:

Fire: Yes Sudden Release of Pressure: No

313 REPORTABLE INGREDIENTS: This material contains Methanol CAS#67-56-1 which is subject to the reporting requirements of Section 313 of SARA Title III and 40 CFR Part 373.

CERCLA (USA - Comprehensive Response Compensation and Liability Act): CAS# 67-56-1: 5000 lb final RQ; 2270 kg final RQ.

California Prop 65, Safe Drinking Water and Toxic Enforcement Act of 1986: None listed.

State Right to Know: Methanol: ILL, MA, NJ, PA, RI; Isopropyl Amine (2-Aminopropane) MA, NJ, PA, RI

PRODUCT NAME: Test C

PRODUCT NUMBER(S): 800-6073 (1006151) DATE: April 20, 2012

# SECTION 15 - REGULATORY INFORMATION (Continued)

WHMIS Classification: B2, D!A, D2A, D2B.

CIDL (Canadian Ingredient Disclosure List): Listed.

CDSL / NDSL (Canadian Domestic Substances List / Non-Domestic Substances List): Listed on CDSL.

EINECS (European Inventory of Existing Commercial Chemical Substances): Referenced.

WGK Water Quality Index: 2 (overall 2 ampoules).

WGN Water Quality Index.	z (overali z allipodies).	
RISK PHRASES:	SYMBOL(S) REQUIRED FOR EU LABEL	SAFETY PHRASES:
R11: Highly flammable. R20/21/22: Harmful by inhalation, in contact with skin and if swallowed. R23/24/25: Toxic by inhalation, in contact with skin and if swallowed. R39/23/24/25: Toxic: danger of very serious irreversible effects through inhalation, in contact with skin and if swallowed.	Xn - Harmful	S1: Keep out of the reach of children. S7: Keep container tightly closed. S9: Keep container in a well ventilated place. S16: Keep away from sources of ignition - No smoking S23: Do not inhale gas/fumes/vapor/spray. S26: In case of contact with eyes, rinse immediately with plenty of water and seek medical advice. S29: Do not empty into drains. S36/37/39: Wear suitable protective clothing, gloves and eye/face protection. S45: In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible). S53: Avoid exposure - obtain special instructions before use.

F - Highly Flammable

# SECTION 16 - OTHER INFORMATION

Legend: N/A = Not Applicable	N/D = Not Determined N/E = Not Established	N/R = Not Reported					
HMIS HAZARD RATINGS	HEALTH:	3	0 = INSIGNIFICANT				
	FLAMMABILITY:	3	1 = SLIGHT				
	PHYSICAL HAZARD:	1	2 = MODERATE				
	PERSONAL PROTECTIVE EQUIPMENT:	В	3 = HIGH				
			4 = EXTREME				

REVISION SUMMARY: Revised 4/20/2012.

## MSDS Prepared by:

ChemTel Inc.

1305 North Florida Avenue Tampa, Florida USA 33602-2902

Toll Free North America 1-888-255-3924 Intl. +01 813-248-0573

Website: www.chemtelinc.com



The information contained herein is believed to be accurate but is not warranted to be so. Data and calculations are based on information furnished by the manufacturer of the product and manufacturers of the components of the product. Users are advised to confirm in advance of need that information is current, applicable and suited to the circumstances of use. Vendor assumes no responsibility for injury to vendee or third persons proximately caused by the material if reasonable safety procedures are not adhered to as stipulated in the data sheet. Furthermore, vendor assumes no responsibility for injury caused by abnormal use of this material even if reasonable safety procedures are followed. Any questions regarding this product should be directed to the manufacturer of the product as described in Section 1.