01-813-248-0585

International

# MATERIAL SAFETY DATA SHEET

SECTION 1 - PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME: Test N

April 20, 2012 PRODUCT NUMBER(S): 800-6083 (1006161) DATE:

TRADE NAME:

Pentazocine (Talwin/Talacen) Test GENERAL USE:

Inorganic Acid Solutions CHEMICAL FAMILY:

PRODUCT DESCRIPTION:

Clear colorless and odorless. - Ampoule 1, Colorless with

possible acrid odor - Ampoule 2

DATE PREPARED: April 20, 2012 MANUFACTURED FOR: SUPERSEDES: October 15, 2008 Safariland LLC

ADDRESS (NUMBER, STREET, P.O. BOX) TELEPHONE NUMBER FOR INFORMATION / Customer Service

13386 International Parkway

(CITY, STATE AND ZIP CODE) COUNTRY

Jacksonville, FL 32218 USA



North America Toll Free **SECTION 2 - HAZARDS IDENTIFICATION** 

ChemTel

#### EMERGENCY OVERVIEW

Highly corrosive liquid. Both liquid and vapors can cause serious damage to tissues. Avoid strong bases and organic compounds. Formaldehyde is toxic to the liver, kidneys, and eyes.

### POTENTIAL HEALTH EFFECTS

#### INHALATION:

Inhalation of vapors may cause severe respiratory irritation, headache, and nausea. Chronic exposure may cause respiratory damage.

Product is highly corrosive, and may seriously burn skin. Use proper gloves and clothing while working with product. Third degree burns can occur, with permanent scarring.

Liquid or vapor may cause severe burns and ulcerations. Use safety glasses; use of a face shield is advisable. Product can cause irreversible damage to eyes.

#### INGESTION:

Product is highly corrosive: ingestion can lead to severe injury, including death. Serious burning, irreversible damage, and extreme pain in gastro-intestinal tract may occur. Formaldehyde ingestion may cause blindness, organ failure, and death.

#### CARCINOGENICITY:

NTP? Yes - Formaldehyde

IARC MONOGRAPHS? Yes - Formaldehyde

OSHA REGULATED? Yes - Formaldehyde

CALIFORNIA, Prop.65?

Yes - Formaldehyde , Sulfuric Acid (mists)

ESIS? Yes - Formaldehyde

BLIC SAFET

800-347-1200

**CHEMTEL 24-HOUR EMERGENCY TELEPHONE NUMBER** 

1-800-255-3924

SECTION 3 - HAZARDOUS INGREDIENTS						
Hazardous Components	% (by Weight)	CAS#	EINECS #	Hazard Symbol	RISK PHRASES (Full Text Section 15)	
Selenious Acid (1st Ampoule)	<1	7783-00-8	231-974-7	Т	R25	
Sulfuric Acid (1st Ampoule)	>95	7664-93-9	231-639-5	C+	R35	
Formaldehyde 37% (1st Ampoule)	<1	50-00-0	200-001-8	Xn	R40, R43	
Nitric Acid (2nd Ampoule)	1-10	7697-37-2	231-714-2	С	R34	

Hazard symbols and risk phrases based on maximum listed concentration of each hazardous ingredient. Notes:

WARNING: THIS PRODUCT CONTAINS CHEMICALS KNOWN TO THE STATE OF CALIFORNIA TO CAUSE CANCER.

## SECTION 4 - FIRST AID MEASURES

## INHALATION:

Place victim in well-ventilated area. If victim is not breathing, perform artificial respiration. Seek immediate medical attention.

#### EYES:

Material can cause severe eye irritation and burns. Flush eyes with a large quantity of water for a minimum of 15 minutes, then seek immediate medical attention. Do not medicate with "over-the-counter" eye products.

#### SKIN:

Product is corrosive and will damage skin and tissues. Use of appropriate gloves and thorough hand-washing with hand cleanser is required. Remove contaminated clothing and rinse thoroughly. If skin is damaged or severely irritated, seek medical help. Safety Showers are highly recommended for use of this product.

Product is highly corrosive; ingestion can lead to severe injury, including death. If victim is able to swallow, give water, then seek immediate medical help.

# **MATERIAL SAFETY DATA SHEET**

PRODUCT NAME: Test N

PRODUCT NUMBER(S): 800-6083 (1006161) DATE: April 20, 2012

### SECTION 5 - FIRE FIGHTING MEASURES

GENERAL HAZARDS:

Material is non-flammable, but heated material can generate corrosive vapors and toxic fumes.

EXTINGUISHING MEDIA:

N/A - product is non-flammable. Choose media for surrounding materials.

FIRE FIGHTING PROCEDURES:

Water may be used to cool product & reduce vapor levels. Self-contained breathing apparatus and turn-out gear are required.

UNUSUAL FIRE AND EXPLOSION HAZARDS:

Toxic and corrosive fumes and/or vapors may form. Self-contained breathing apparatus is required. Decontamination of fire-fighting gear may be needed.

HAZARDOUS COMBUSTION PRODUCTS:

May produce fumes containing selenium compounds, which are highly toxic. Self-contained breathing apparatus is required for fire-fighting purposes.

### SECTION 6 - ACCIDENTAL RELEASE MEASURES

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED:

AVOID BREATHING VAPORS. DO NOT ADD WATER TO SPILL!!! Sequester leak or spill. Use sand or kaolin to absorb spill. Do not discharge into waterways or sewer systems.

# SECTION 7 - HANDLING AND STORAGE

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE:

Store in cool, dry, place. Avoid moisture.

SECTION 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION								
	NIOSH			ACGIH		OSH	OSHA	
HAZARDOUS COMPONENTS	TWA ppm	TWA mg/m3	STEL ppm	STEL mg/m3	TLV/TWA ppm	TWA mg/m3	STEL ppm	STEL mg/m3
Selenious Acid (1st Ampoule)	MAK: (respirable fraction) 0.05 mg/m <sup>3</sup>			0.2				
Sulfuric Acid (1st Ampoule)		1			0.2			1
Formaldehyde 37% (1st Ampoule)						0.5		5
Nitric Acid (2nd Ampoule)	2	5	4	10	2	5	2	5

### PERSONAL PROTECTION

RESPIRATORY PROTECTION:

Generally not needed, as ampoules are small and used immediately. Use approved NIOSH respirator if TLV levels are exceeded.

PROTECTIVE GLOVES:

Wear protective gloves while working with product.

EYE PROTECTION:

Chemical goggles are required to prevent potential eye contact, irritation or injury.

OTHER PROTECTIVE CLOTHING OR EQUIPMENT:

Wear appropriate protective clothing and boots as required to prevent skin contact.

WORK / HYGIENIC PRACTICES:

Use good industrial hygiene.

SECTION 9-PHYSICAL AND CHEMICAL PROPERTIES				
APPEARANCE AND ODOR	VAPOR PRESSURE			
Clear colorless and odorless Ampoule 1, Colorless with possible acrid odor - Ampoule 2	1 mm Hg @ 145.8°F(63.2°C) - Ampoule 1, ND - Ampoule 2			
рН	SPECIFIC GRAVITY (WATER = 1)			
<1.0	1.83 - Ampoule 1, 1.0-1.05 - Ampoule 2			
BOILING POINT / BOILING RANGE	SOLUBILITY IN WATER			
290°F (143°C) - Ampoule 1, 212°F (100°C) - Ampoule 2	Complete			
FLASH POINT	VISCOSITY			
None	N/D			
FLAMMABLE LIMITS	VAPOR DENSITY (AIR = 1)			
LEL: <b>N/D</b> UEL: <b>N/D</b>	~3.4 for Sulfuric Acid (Ampoule 1), ND (Ampoule 2)			
AUTO-IGNITION TEMPERATURE	EVAPORATION RATE (WATER = 1)			
NE	N/D			

# MATERIAL SAFETY DATA SHEET

PRODUCT NAME: Test N

PRODUCT NUMBER(S): 800-6083 (1006161) DATE: April 20, 2012

SECTION 10 - STABILITY AND REACTIVITY

STABILITY STABLE X CONDITIONS TO AVOID:

Extreme Heat (above 120°F)

INCOMPATIBILITY (MATERIALS TO AVOID):

Alkalis, metals, halogenated salts (fluorides, chlorides, bromides, iodides, chlorates, perchlorates, etc.), organic compounds, water (will generate heat).

HAZARDOUS DECOMPOSITION OR BYPRODUCTS:

Selenium compounds, sulfur compounds, nitrogen compounds.

HAZARDOUS POLYMERIZATION: CONDITIONS TO AVOID:

Will Not Occur. None Related to Polymerization.

SECTION 11 - TOXICOLOGICAL INFORMATION					
CAS # EINECS #	LD50 of Ingredient (Specify Species and Route)	LC50 of Ingredient (Specify Species)			
7783-00-8	11 mg/kg (INTRAVENOUS MOUSE)	NR			
231-974-7	TT Hig/kg (INTKAVENCOS, MOOSE)				
7664-93-9	250 ma/kg (ODAL DAT)	320 mg/m3 / 2 Hours			
231-639-5	330 Hig/kg (OKAL, KAT)	(INHALATION, MOUSE)			
50-00-0	100 mg/kg (OPAL_PAT)	203 mg/m3 / Unknown Time			
200-001-8	- 100 mg/kg (ORAL, KAT)	(INHALATION, MOUSE)			
7697-37-2	Lowest published lethal dose: 430	Inhalation rat LC50: 244 ppm			
231-714-2	mg/kg (human)	(NO2)/ 30 Minutes)			
	CAS # EINECS # 7783-00-8 231-974-7 7664-93-9 231-639-5 50-00-0 200-001-8 7697-37-2	CAS # LD50 of Ingredient (Specify Species and Route)  7783-00-8 231-974-7 7664-93-9 231-639-5 50-00-0 200-001-8 7697-37-2 Lowest published lethal dose: 430			

# SECTION 12 - ECOLOGICAL INFORMATION

Toxic to aquatic organisms.

### SECTION 13 - DISPOSAL CONSIDERATIONS

WASTE DISPOSAL METHOD:

Do not dispose into waterways or sewers. Waste may be considered hazardous; the user has the responsibility of compliance with federal, state, and local regulations concerning waste disposal.

## **SECTION 14 - TRANSPORT INFORMATION**

GROUND SHIPMENT WITHIN USA (DOT):

PROPER SHIPPING NAME: None - Exempted Qty.

CLASS/ PACK GROUP/ LABELING: Class 8 with Excepted Qty. marking on package. No class 8 label required.

NOTES: When shipped under 49CFR173.4a, This product is exempt from other labeling and waybill requirements.

GROUND SHIPMENTS TO AND WITHIN CANADA (TDG):

PROPER SHIPPING NAME: None - Limited Quantity (within Canada), See above for US to Canada

CLASS/ PACK GROUP/ LABELING: Phrase "Ltd. Qty." on package. No additional requirements.

NOTES: TDG only used for shipment within Canada, shipments from the US can follow DOT regulations. See TDG Sections 1.17

and 9.

AIR SHIPMENTS (ICAO/IATA):

PROPER SHIPPING NAME: None - (Classified under UN2031 Nitric Acid Solution <20% Nitric acid &

UN 1830 Sulfuric Acid - Overall Excepted Qty. E2)

CLASS/ PACK GROUP/ LABELING: Class 8 with Excepted Qty. marking on package. No class 8 label required.

NOTES: This product is exempt from other labeling and waybill requirements.

OCEAN SHIPMENTS (IMDG):

PROPER SHIPPING NAME: None

CLASS/ PACK GROUP/ LABELING: Class 8 with Excepted Qty. marking on package. No class 8 label required.

NOTES: Shipping Paper required with statement "Dangerous Goods in Excepted Quantities" and number of packages.

ALL SHIPMENTS EXCEEDING EXCEPTED QUANTITY / ALTERNATIVE SHIPPING INFORMATION:

PROPER SHIPPING NAME: UN 3316. Chemical Kit

CLASS/ PACK GROUP/ LABELING: Class 9, Pack Group III. Miscellaneous Label

NOTES: Full documentation required.

Note: Transportation information provided is for reference only. Client is urged to consult CFR 49 parts 100 - 177, IMDG, IATA, TDG & UN information manuals for detailed regulations and exceptions covering specific container sizes, packaging materials and methods of shipping. Information above does not account for overpacks or outer packings with multiple hazardous materials; consult shipper when multiple materials are shipped. Consult regulations for maximum outer packaging and overpack requirements

# MATERIAL SAFETY DATA SHEET

PRODUCT NAME: Test N

PRODUCT NUMBER(S): 800-6083 (1006161) DATE: April 20, 2012

SECTION 15 - REGULATORY INFORMATION

TSCA (USA - Toxic Substance Control Act): Yes

SARA TITLE III (USA - Superfund Amendments and Reauthorization Act): Yes - 302 and 313 (Nitric Acid)

302 and 313 (Selenious Acid) 302 and 313 (Sulfuric Acid)

S45: In case of accident or if you feel unwell, seek medical advice immediately (show the label where

Acute Health: Yes Chronic Health: Yes
Fire: No Sudden Release of Pressure: No
Reactive: Yes

313 REPORTABLE INGREDIENTS: This material contains Formaldehyde, Nitric Acid, Sulfuric Acid, and

Selenious Acid, which are subject to the reporting requirements of Section

possible).

313 of SARA Title III and 40 CFR Part 373.

CERCLA (USA - Comprehensive Response Compensation and Liability Act): Yes - All ingredients

State Right to Know: Sulfuric acid: MA,NJ, PA; Selenious acid: MA, NJ, PA; Formaldehyde:CA, ILL, MA,NJ, PA, RI. Nitric acid: ILL, MA,MN,NJ,PA,RI

California Prop 65, Safe Drinking Water and Toxic Enforcement Act of 1986: Yes - Formaldehyde, Sulfuric Acid (Mists)-Cancer.

(Mists)-Carice

CCPR (Canadian Controlled Products Regulations): Yes - Corrosive (Section 65, Class E)

CIDL (Canadian Ingredient Disclosure List): Yes - Selenious Acid, Sulfuric Acid, Formaldehyde, Nitric Acid CDSL / NDSL (Canadian Domestic Substances List / Non-Domestic Substances List): Referenced on CDSL

EINECS (European Inventory of Existing Commercial Chemical Substances): Referenced.

/VGK	Water	Quality	Index:	2

RISK PHRASES:	SYMBOL(S) REQUIR	RED FOR EU LABEL	SAFETY PHRASES:
R35 : Causes severe burns.			S1/2 : Keep locked up and out of the reach of
R40 : Limited evidence of			children.
carcinogenic effect.			S26 : In case of contact with eyes, rinse
R43 : May cause sensitization by skin			immediately with plenty of water and seek medical
contact.			advice.
	302		S30 : Never add water to this product.

C+ - CORROSIVE Xn-HARMFUL

# SECTION 16 - OTHER INFORMATION

# Legend:N/A = Not ApplicableN/E = Not EstablishedN/D = Not DeterminedN/R = Not Reported

#### REVISION SUMMARY:

Revised 4/20/2012.

#### MSDS Prepared by:

ChemTel Inc.

1305 North Florida Avenue Tampa, Florida USA 33602-2902

Toll Free North America 1-888-255-3924 Intl. +01 813-248-0573

Website: www.chemtelinc.com



The information contained herein is believed to be accurate but is not warranted to be so. Data and calculations are based on information furnished by the manufacturer of the product and manufacturers of the components of the product. Users are advised to confirm in advance of need that information is current, applicable and suited to the circumstances of use. Vendor assumes no responsibility for injury to vendee or third persons proximately caused by the material if reasonable safety procedures are not adhered to as stipulated in the data sheet. Furthermore, vendor assumes no responsibility for injury caused by abnormal use of this material even if reasonable safety procedures are followed. Any questions regarding this product should be directed to the manufacturer of the product as described in Section 1.